

# INDUSTRIAL SAW BLADES

## STANDARD PURPOSE CUT-OFF SAWS

Triple Chip

For fine finishing cuts in plywood, veneered panel, masonite coated or uncoated, crosscutting in hard or soft woods, plexi-glass over 1/2 inch thickness. Ideal for table saws. Please note triple chip grind recommended for cutting all types of abrasive materials such as chipboard or high pressure laminates.

Saw No.	Diameter	Plate Thickness	Kerf	Bore	Hook	Teeth
SP71456T	7-1/4"	.072	.102	Univ.	10°	56
SP860T	8"	.085	.125	5/8"	10°	60
SP960T	9"	.085	.125	5/8"	10°	60
LSP1060T	10"	.085	.125	5/8"	10°	60
*PSP1060T	10"	.085	.125	5/8"	10°	60
SP1260T	12"	.095	.135	1"	10°	60
SP1460T	14"	.109	.155	1"	10°	60
SP1660T	16"	.109	.155	1"	10°	60
SP1860T	18"	.134	.180	1"	10°	60

\*With copper plugs.

## SPECIAL PURPOSE CUT-OFF SAWS

Alternate Top Bevel

For the smoothest possible finish in plywood, veneer, laminated panels, coated hardboard, plexi-glass up to 3/8 inch thickness, for crosscutting of both hard and soft woods up to 3/4 inch thick.

Saw No.	Diameter	Plate Thickness	Kerf	Bore	Hook	Teeth
SPE1080A	10"	.085	.125	5/8"	5°	80
SPE1280A	12"	.095	.135	1"	5°	80
SPE1210A	12"	.095	.135	1"	5°	100
SPE1480A	14"	.109	.150	1"	10°	80
SPE1410A	14"	.109	.150	1"	5°	100
SPE1680A	16"	.109	.150	1"	10°	80
SPE1610A	16"	.120	.160	1"	5°	100
SPE1620A	16"	.120	.160	1"	5°	120
SPE1880A	18"	.134	.175	1"	10°	80
SPE1810A	18"	.134	.175	1"	10°	100
SPE1820A	18"	.134	.175	1"	10°	120

## SPECIAL PURPOSE CUT-OFF SAWS

Triple Chip

For the smoothest possible finish in plywood, veneer, laminated panels, coated hardboard, plexi-glass up to 3/8 inch thickness, for crosscutting of both hard and soft woods up to 3/4 inch thick. Please note triple chip grind recommended for cutting all types of abrasive materials such as chipboard or high pressure laminates.

Saw No.	Diameter	Plate Thickness	Kerf	Bore	Hook	Teeth
SPE1080T	10"	.085	.125	5/8"	5°	80
SPE1280T	12"	.095	.135	1"	5°	80
SPE1210T	12"	.095	.135	1"	5°	100
SPE1480T	14"	.109	.150	1"	10°	80
SPE1410T	14"	.109	.150	1"	5°	100
SPE1680T	16"	.109	.150	1"	10°	80
SPE1610T	16"	.120	.160	1"	5°	100
SPE1620T	16"	.120	.160	1"	5°	120
SPE1880T	18"	.134	.175	1"	10°	80
SPE1810T	18"	.134	.175	1"	10°	100
SPE1820T	18"	.134	.175	1"	10°	120