

DOUBLE FACE LAMINATE SAWS

30° ATB

Smoothest cutting saw for double sided materials such as Melamine. Korton & Veneer. Can be used on radial or table saws.

Saw No.	Diameter	Plate Thickness	Kerf	Bore	Hook	Teeth
DFL86030	8"	.085	.115	5/8"	-5°	60
DFL108030	10"	.085	.115	5/8"	-5°	80
DFL121030	12"	.095	.125	1"	-5°	100
DFL141030	14"	.118	.148	1"	-2°	100
DFL162030	16"	.120	.150	1"	-2°	120

NOTE: Not recommended for machines with power feeds or if material is being stacked.

MICRO-5 DOUBLE FACE LAMINATE SAWS

30° ATB

Smoothest cutting saw for double sided materials such as Melamine. Kortron & Veneer. Can be used on radial or table saws. Extra hard MICRO-5 tips last 3-5 times longer than normal carbide.

Saw No.	Diameter	Plate Thickness	Kerf	Bore	Hook	Teeth
*DFL2206430	220mm	.085	.125	30mm	-5°	64
DFL1080305	10"	.085	.115	5/8"	-5°	80
**DFL3001030	300mm	.085	.115	30mm	-5°	100
DFL1210305	12"	.095	.125	1"	-5°	100

*For Holz-her - 2 ph 7mm dia. on 42mm B/C

**For Striebig

NOTE: Not recommended for machines with power feeds or if material is being stacked.

DOUBLE FACE LAMINATE SAWS

TC 45

The perfect saw for the best possible cutting of formica and Melamine laminated panels. These blades can perform equally as well on both radial or table saws.

Saw No.	Diameter	Plate Thickness	Kerf	Bore	Hook	Teeth
DFL860	8"	.085	.115	5/8"	-5°	60
DFL960	9"	.085	.115	5/8"	-5°	60
DFL1080	10"	.085	.115	5/8"	-5°	80
DFL1210	12"	.095	.125	1"	-5°	100
DFL1410	14"	.120	.150	1"	-2°	100
DFL1620	16"	.120	.150	1"	-2°	120

NOTE: Not recommended for machines with power feeds or if material is being stacked.